



# Network Monitoring and Management

## Cisco Configuration



These materials are licensed under the Creative Commons *Attribution-NonCommercial 3.0 Unported* license (<http://creativecommons.org/licenses/by-nc/3.0/>) as part of the ICANN, ISOC and NSRC Registry Operations Curriculum.

# Topics

- CLI modes
- Accessing the configuration
- Basic configuration (hostname and DNS)
- Authentication and authorization (AAA)
- Log collection
- Time Synchronization (date/timezone)
- SNMP configuration
- Cisco Discovery Protocol (CDP)

# CLI Modes

## User EXEC

- Limited access to the router
- Can show some information but cannot view nor change configuration

```
rtr>
```

## Privileged EXEC

- Full view of the router's status, troubleshooting, manipulate config, etc.

```
rtr> enable
```

```
rtr#
```

# Accessing the router

## Before setting up SSH

- telnet 10.10.x.254
- login "cisco" and "cisco" (user and password)

## Privileged user can go to privileged mode:

- rtr> enable (default password is "cisco")
- rtr# configure terminal
- rtr(config)#

## Type in configuration commands

## Exit and save the new configuration

- rtr(config)# end
- rtr# write memory

# Accessing the configuration

There are two configurations:

- ***Running config*** is the actual configuration that is active on the router and stored in RAM (will be gone if router is rebooted):

```
rtr# configure terminal          (conf t)
rtr(config)# end
rtr# show running-config        (show run)
```

- ***Startup config***

Stored in NVRAM (Non-Volatile RAM):

```
rtr# copy running-config startup-config  (or)
rtr# write memory                        (wr mem)
rtr# show startup-config                 (sh start)
```

# Basic configuration (hostname and DNS)

- **Assign a name**

```
rtr(config)# hostname rtrX
```

- **Assign a domain**

```
rtr(config)# ip domain-name ws.nsrc.org
```

- **Assign a DNS server**

```
rtr(config)# ip name-server 10.10.0.241
```

- **Or, disable DNS resolution**

```
rtr(config)# no ip domain-lookup
```

if no dns this is *very useful* to avoid long waits

# Authentication and authorization

## Configuring passwords:

- Passwords stored as a hash

### Example:

```
# enable secret 0 cisco
```

```
# user admin secret 0 cisco
```

# Authentication and authorization

## Configuring SSH with a 2048 bit key (at least 768 for OpenSSH clients)

```
rtr(config)# aaa new-model  
rtr(config)# crypto key generate rsa (key size prompt)
```

## Verify key creation:

```
rtr# show crypto key mypubkey rsa
```

## Optionally register events. Restrict to only use SSH version 2 :

```
rtr(config)# ip ssh logging events  
rtr(config)# ip ssh version 2
```

## Use SSH, disable *telnet* (only use telnet if no other option):

```
rtr(config)# line vty 0 4  
rtr(config)# transport input ssh
```

**Note:** on CatOS, you'll need to explicitly disable telnet



# Log collection (syslog\*)

## Send logs to the *syslog* server:

```
rtr(config)# logging 10.10.x.x
```

## Identify what channel will be used (local0 to local7):

```
rtr(config)# logging facility local5
```

## Up to what priority level do you wish to record?

```
rtr(config)# logging trap <logging_level>
```

<0-7>	Logging severity level	
emergencies	System is unusable	(severity=0)
alerts	Immediate action needed	(severity=1)
critical	Critical conditions	(severity=2)
errors	Error conditions	(severity=3)
warnings	Warning conditions	(severity=4)
notifications	Normal but significant conditions	(severity=5)
informational	Informational messages	(severity=6)
debugging	Debugging messages	(severity=7)

# Time synchronization

**It is essential that all devices in our network are time-synchronized**  
**In config mode:**

```
rtr(config)# ntp server pool.ntp.org  
rtr(config)# clock timezone <timezone>
```

**To use UTC time:**

```
rtr(config)# no clock timezone
```

**If your site observes daylight savings time you can do:**

```
rtr(config)# clock summer-time recurring last Sun Mar 2:00 last Sun Oct 3:00
```

**Verify:**

```
rtr# show clock
```

```
22:30:27.598 UTC Tue Feb 15 2011
```

```
rtr# show ntp status
```

```
Clock is synchronized, stratum 3, reference is 4.79.132.217  
nominal freq is 250.0000 Hz, actual freq is 249.9999 Hz, precision is 2**18  
reference time is D002CE85.D35E87B9 (11:21:09.825 CMT Tue Aug 3 2010)  
clock offset is 2.5939 msec, root delay is 109.73 msec...
```

# SNMP configuration

## Start with SNMP version 2

- It's easier to configure and understand
- Example:

```
rtr(config)# snmp-server community NetManage ro 99  
rtr(config)# access-list 99 permit 10.10.0.0 0.0.255.255
```

# SNMP configuration

**From a Linux machine (once snmp utils are installed),  
try:**

```
snmpwalk -v2c -c NetManage 10.10.x.254 sysDescr
```

# Cisco Discovery Protocol (CDP)

**Enabled by default in most modern routers**

**If it's not enabled:**

```
Rtr(config)# cdp enable
```

```
Rtr(config)# cdp run
```

 (in older CISCO IOS versions)

**To see existing neighbors:**

```
rtr# show cdp neighbors
```

**Tools to visualize/view CDP announcements:**

*tcpdump*

*cdpr*

*wireshark*

*tshark*

# Enabling NetFlow (traffic flow export)

**Configure FastEthernet 0/0 to generate netflow and export flows to 10.10.0.250 on port 9996:**

```
rtr# configure terminal
rtr(config)# interface FastEthernet 0/0
rtr(config-if)# ip flow ingress
rtr(config-if)# ip flow egress
rtr(config-if)# exit
rtr(config-if)# ip flow-export destination 10.10.0.250 9996
rtr(config-if)# ip flow-export version 5
rtr(config-if)# ip flow-cache timeout active 5
```

This breaks up long-lived flows into 5-minute fragments. You can choose any number of minutes between 1 and 60. If you leave it at the default of 30 minutes your traffic reports will have spikes.

**Note:** Newer version of Cisco IOS have changed this syntax.

# Enabling NetFlow cont.

```
rtr(config)# snmp-server ifindex persist
```

Ensures that counter index numbers persist across reboots

Now configure how you want the ip flow top-talkers to work:

```
rtr(config)#ip flow-top-talkers
rtr(config-flow-top-talkers)#top 20
rtr(config-flow-top-talkers)#sort-by bytes
rtr(config-flow-top-talkers)#end
```

Verify what we've done

```
rtr# show ip flow export
rt# show ip cache flow
```

See your "top talkers" across your router interfaces:

```
rtr# show ip flow top-talkers
```

# Questions?



For more information, check out

[http://www.cisco.com/en/US/docs/ios/12\\_2/configfun/configuration/guide/ffun\\_c.html](http://www.cisco.com/en/US/docs/ios/12_2/configfun/configuration/guide/ffun_c.html)